



# BioSeal™

## TECHNICAL INFORMATION 01.10.2007 MOULD PROTECTION

### Product description

Water-based dispersion of styrene acrylate with very good penetrating properties and a high efficiency against micro-organisms.

### Range of applications

As a primer on badly affected surfaces and absorbing surfaces before BioRid treatment.

### Pretreatment

The surface should be free from contamination such as soot, oil and grease. Soiled and affected surfaces must be cleaned before using BioSeal.

### Application

Spray, brush or roller.

---

## Technical information

---

|                               |                           |
|-------------------------------|---------------------------|
| Density                       | 1,01 g/cm <sup>3</sup>    |
| Solids content by volume      | 13%                       |
| Viscosity at 20°C             | 30 mPas                   |
| Coat thickness, wet           | 100 µm                    |
| Coat thickness, dry           | 13 µm                     |
| Effective consumption         | 2-10 m <sup>2</sup> /l    |
| Drying time at 20°C, 55% r.h. | 1-2 hours                 |
| Cleaning                      | Water                     |
| Appearance/colour             | Uncoloured, clear varnish |
| Thinner                       | Water                     |
| Flash point                   | Incombustible             |

**Frost free storing required!**

**KEFA International Handels GmbH**

---

Tel.: (+ 49) 45 26 - 17 06  
Fax: (+ 49) 45 26 - 5 27  
KEFA.International@t-online.de  
www.kefa-international.com

Geschäftsführer:  
J.-E. Rollen, P. Andersson  
HRB 1696, Amtsgericht Plön  
Sitz der Gesellschaft: Ascheberg

Bankverbindung  
Förde Sparkasse  
BLZ 210 501 70  
Kto.-Nr. 100 11 48

IBAN-NR.: DE23 2105 1580 0001 0011 48  
BIC: HSHNDEH1PLN  
USt-Steuer-Nr.: 19 29 82 43 80  
USt-IdNr.: DE 13 48 97 79 3