



GrafoSeal™

TECHNICAL INFORMATION 11.10.2007

Primer

Product description

Water-based dispersion of styrene acrylate with very good penetrating properties.

Pretreatment

The surface should be free from contamination such as soot, oil and grease. Mould affected surfaces should be cleaned with BioWash.

Range of applications

As a primer on absorbing surfaces before GrafoTherm treatment.

Application

Spray, brush or roller.

Technical information

Density	1,01 g/cm ³
Solids content by volume	13 %
Viscosity at 20°C	30 mPas
Coat thickness, wet	100 µm
Coat thickness, dry	13 µm
Effective consumption	2-10 m ² /l
Drying time at 20°C, 55% r.h.	1-2 hours
Cleaning	Water
Appearance/colour	Uncoloured, clear varnish
Thinner	Water
Flash point	Incombustible

Frost free storing required!

KEFA International Handels GmbH

Tel.: (+ 49) 45 26 - 17 06
Fax: (+ 49) 45 26 - 5 27
KEFA.International@t-online.de
www.kefa-international.com

Geschäftsführer:
J.-E. Rollen, P. Andersson
HRB 1696, Amtsgericht Plön
Sitz der Gesellschaft: Ascheberg

Bankverbindung
Förde Sparkasse
BLZ 210 501 70
Kto.-Nr. 100 11 48

IBAN-NR.: DE23 2105 1580 0001 0011 48
BIC: HSHNDEH1PLN
USt-Steuer-Nr.: 19 29 82 43 80
USt-IdNr.: DE 13 48 97 79 3